

WASTEWATER QUALITY AND POLLUTION LOAD OF EACH STAGE IN TEMPEH PRODUCTION

by Vita Pramaningsing

Submission date: 13-Dec-2022 03:29PM (UTC+0800)

Submission ID: 1980012545

File name: Urbanenvirotech2022.pdf (1.15M)

Word count: 4898

Character count: 26331



WASTEWATER QUALITY AND POLLUTION LOAD OF EACH STAGE IN TEMPEH PRODUCTION

Vita Pramaningsih^{1*}, Hansen Hansen¹, Sarva Mangala Praveena²,
Ucik Ika Fenti Styana³

¹Department of Environmental Health, Faculty of Public Health, Universitas Muhammadiyah, Samarinda, East Kalimantan, Indonesia

²Department of Environmental and Occupational Health, Universiti Putra Malaysia, Selangor, Malaysia

³Department Energy Engineering, Institut Teknologi Yogyakarta, Yogyakarta, Indonesia

*Corresponding author: vp799@umkt.ac.id

ABSTRACT

Aim: This study is purpose to understand the chemical and physical characteristics and pollution load in each step of tempeh wastewater: washing, boiling, soaking and mixing. However, wastewater from tempeh production is discharge to river directly which considered as environmentally damaging. However, the characteristics of wastewater from tempeh production and its level of environmental impacts to environment are limitedly studied. **Methodology and Results:** Tempeh wastewater was analyzed in chemical and physical parameters. Chemical characteristics analyzed are pH, Biological Oxygen Demand (BOD) and Chemical Oxygen Demand (COD). The physical parameter analyzed is Total suspended Solid (TSS). Pollution load calculated by deviation maximum pollution load and pollution load existing. Result of this study findings indicated that the highest BOD 299.40 mg/L and COD 540.66 mg/L was found in soaking step compared to other steps in tempeh production. Highest TSS 655.20 mg/L was found in boiling step. The pH values in all steps were acidic 4 and 5. Allocation Pollution load of: TSS overall exceeded the capacity, BOD and COD overall exceeded the capacity except in washing step (BOD 304.39 kg/day and COD 857.78 kg/day). **Conclusion, significance and impact of study:** The Highest TSS of tempeh wastewater processes was in boiling step while the highest organic matter was detected in soaking. Further for whole pH were acidic and exceeded the standard. Allocation of pollution load for TSS, BOD and COD exceed the standard except for BOD and COD in washing waste. Overall tempeh wastewater needs treatment to prevent river pollution.

MANUSCRIPT HISTORY

- Received January 2022
- Revised April 2022
- Accepted June 2022
- Available online October 2022

KEYWORDS

- Biological oxygen demand (BOD)
- Chemical oxygen demand (COD)
- pH
- Pollution load
- Total suspended solid (TSS)

1. INTRODUCTION

Tempeh is one of traditional and favorite foods in Indonesia from soybean fermentation. Tempeh is a healthy food holds more protein, dietary fibre and vitamins (Wijaya, 2019). Soybean is a protein source in foods production that a lot kind of processed as fermented (tempeh, natto, miso, soy sauce) and unfermented (soy milk and tofu) (Chua and Liu, 2019; Puspawati and Soesilo, 2018). Tempeh is produced by fermentation, it improved nutritional value, enhance proteins, carbohydrates and lipids (Santhirasegaram *et al.*, 2016). It's also low cost, health promoting and sustainable food production technology to produce protein-rich foods (Ahn-an-winarno *et al.*, 2021). Many home industries produce tempeh in Indonesia.

In general, tempeh production is conducted at household scale without wastewater treatment to treat their waste. Subsequently tempeh production wastewater is streamed directly into drainage and lastly to river. The direct discharge of tempeh production wastewater without any treatment has affected the river water quality which is used as raw drinking water supply in Samarinda. Furthermore, Karang Mumus River that through the Samarinda City has indicated Biological Oxygen Demand (BOD) and Chemical Oxygen Demand (COD) have exceeded the what standards which the source of pollution load capacity comes from domestic activities such tempeh production (Pramaningsih *et al.*, 2020).

Soybean wastewater such as tempeh has high organic matter and COD content (Guo *et al.*, 2018). Wastewater treatment to reduce COD can produce a bioenergy as biogas from methane. It is mean if use traditional or minimum treatment will be wasted the bioenergy (Yu *et al.*, 2017). Soybean Processing Waste (SPW) in anaerobic digestion treatment can produce biogas. SPW/hay ratio give significant effect on daily cumulative methane (Zhu *et al.*, 2014). Thus, the study aims to identify the chemical and physical characteristics and pollution load in each processes of tempeh production. Understanding of tempeh wastewater characteristics will be able to provide guidance on wastewater treatment and potential to produce biogas from methane.

2. RESEARCH METHODOLOGY

Tempeh production process consists of: (1) soybeans boiled and soaked overnight then washed, (2) breaking soybean to be two parts then the skin separate by washing it, (3) fermentation process and packaging, (4) keep Tempeh around two days to get good product. Detail of

tempeh production processes and point source of wastewater chose to measure, show in Figure 1. Tempeh wastewater samples were collected was taken from each processes that produce a lot of wastewater: washing, boiling, soaking and mixing (mixing waste from all process) in tempeh production.

Tempeh wastewater was analyzed for chemical and physical characteristic. The chemical characteristics analyzed are pH, Biological Oxygen Demand (BOD) and Chemical Oxygen Demand (COD). pH was measured using pH meter, BOD using SNI 6989.72:2009 method and COD using SNI 6989.2: 2019 method. The physical parameter analyzed is Total Suspended Solid (TSS) and analyzed using SNI 6989.3: 2019 method. Furthermore discharge was calculate by batch system at the time of production run in the morning. This is a home industry that run production just in the morning every day.

The physical and chemical parameters were compared with the standards from region government regulation of East Kalimantan Province No. 2 Years 2011 regarding water quality management and water pollution control (Government regulation, 2011). Pollution load was calculated using the Indonesian Ministry of Environmental No. 110 Years 2003 about Guidelines for Determination of Load Capacity Water Pollution in Water Source (State Minister of Environment, 2003) as in Equation 1.

$$\text{Pollution Load Existing} = Q \times C \quad (1)$$

Pollution Load Existing (kg/day)

Q = Discharge (m³/sec)

C = Concentration of pollution (mg/L)

Load Capacity Water Pollution is counted by calculate maximum pollution load from standard concentration of pollution was regulation allowed. Afterward obtained allocation of pollution load by calculate deviation maximum pollution load and pollution load existing. If obtained minus it means the load capacity water pollution has exceeded.




Figure 1 Tempeh production processes and samples measured

3

3. RESULTS AND DISCUSSION

3.1 Wastewater Quality of TSS, BOD, COD and pH

Table 1 shows the Total Suspended Solid (TSS) in each step processing from washing to mixing included result of mixing waste from all process. TSS contents in all processes have exceed the

2

what standard and the highest TSS was in boiling process (655,2 mg/L). TSS affect to the water quality of turbidity in the water body as river. It is impact to inhibit the penetration sunlight to the water body and disturb photosynthesis in the waters caused decrease Dissolved Oxygen (DO) (Puspawati and Soesilo, 2018; Seroja, Effendi and Hariyadi, 2018). The biological degradation process of organic matter was determined by DO contents (Wang *et al.*, 2019).

Table 1 Total suspended solid (TSS) contents

Source of Tempeh Wastewater	TSS (mg/L)	Standard (mg/L)
Washing	223.20	200
Boiling	655.20	200
Soaking	370.00	200
Mixing	194.40	200

Table 2 shows BOD contents in Tempeh wastewater in each process of tempeh production. BOD content in boiling, soaking and mixing waste from all process exceed the standard except in washing process and the highest BOD was in soaking process indicating that the organic matter soaking is high in tempeh wastewater (Wang and Serventi, 2019). BOD content in waste water means organic matter pollutant (Mamun, Lee and An, 2018).

Table 2 Biological oxygen demand (BOD) contents

Source of Tempeh Wastewater	BOD (mg/L)	Standard (mg/L)
Washing	114.77	50
Boiling	174.65	50
Soaking	299.40	50
Mixing	264.47	50

Table 3 shows COD level in each process of tempeh wastewater and mixing waste from all process. COD content in boiling, soaking and mixing waste from all process exceed the standard except in washing process and highest COD was showed in soaking. Moreover, COD and BOD values are similar as oxygen demand to degrade organic matter in difference process (Mamun, Lee and An, 2018; Wang and Serventi, 2019; Pramaningsih *et al.*, 2020). Soaking wastewater contain of higher organic matter than others.

Table 3 Chemical Oxygen Demand (COD) Contents

Source of Tempeh Wastewater	COD (mg/L)	Standard (mg/L)
Washing	200.72	100
Boiling	351.54	100
Soaking	540.66	100
Mixing	403.02	100

Table 4 shows TSS, BOD and COD contents in each tempeh processing step. The highest TSS in boiling process while the highest of BOD and COD is in soaking process. It is similar with the other researcher, where wastewater of soybean food in each step processing has difference characteristic especially in soaking and cooking water have high COD and BOD [15]. The others source of tempeh wastewater have low of pollutants, it can be treated by minimum treatment to get the standard. Then the wastewater high organic matter can be reduced by aerobic or anaerobic digestion. Soybean wastewater characterized is high organic was composed soluble protein and carbohydrates, with high COD (Guo *et al.*, 2018). Reducing COD of Soybean wastewater used hybrid system by direct feeding is more affective without dilution (Song *et al.*, 2019). Soybean wastewater treatment by anaerobic digester produce methane about 55% and COD removal about 80% (Yu, 2015). Anaerobic digestion processes from tempeh wastewater treatment produced methane 8720 mL and COD removal 67.7% (Fransiscus and Simangunsong, 2021). The other soybean wastewater treatment to reduce COD use biological process using *Aspergillus niger* pelletization technology found 98.11% COD removal (Zhang, Zhang and Diao, 2017).

BOD and COD content in the wastewater will impact to the Dissolved Oxygen (DO) that it is support the healthy aquatic ecosystem. Beside that DO content also influence the biological organic degradation process changes in aerobic or anaerobic organisms work (Wang *et al.*, 2019). Decreasing of DO due to the organic matter had increased in the water (Raudsepp *et al.*, 2019). Organic matter from the waste of human activities or industries influence to river water quality especially for BOD and COD will be high (Pramaningsih *et al.*, 2020).

Table 4 TSS, BOD and COD contents in each soybean processes

Source of Tempeh Wastewater	TSS (mg/L)	BOD (mg/L)	COD (mg/L)
Washing	223.20	114.77	200.72
Boiling	655.20	174.65	351.54
Soaking	370.00	299.40	540.66
Mixing	194.40	264.47	403.02

The content of pH in each soybean processing step is showed in Table 5. The lowest pH was showed in soaking and mixing at 4.0 and can influence microalgae life in wastewater treatment. Low pH and sufficiently phosphorous resources determine efficient COD removal by microalgae (Song *et al.*, 2019) but pH adjustment to neutral at 7.0 guaranteed growth of microalgae (Song *et al.*, 2020). COD removal by reactor is effective in pH at 7.0-7.4 (Guo *et al.*, 2018).

Table 5 pH contents in each soybean processes

Source of Tempeh Wastewater	pH	Standard
Washing	5	6
Boiling	5	6
Soaking	4	6
Mixing	4	6

3.2 Pollution Load of TSS

Pollution load existing, maximum pollution load and allocation pollution load of TSS from tempeh industry wastewater showed in Table 6, 7, and 8. Pollution load existing is amount of a polluting element contained in water or wastewater. Maximum pollution load is the standard maximum polluting allowed in wastewater discarded to the environment. Pollution load was calculated by multiplication of discharge and the pollutant concentration. Deviations of both are allocation of pollution load that will be allowed while getting positive value and need improvement while getting negative value. It used for monitoring water pollution source before discarded to the river or environment.

Wastewater Quality and Pollution Load of Each Stage in Tempeh Production

Pramaningsih, Hansen, Praveena, Styana
p-ISSN 2579-9150; e-ISSN 2579-9207, Volume 5, Number 3, page 209-222, October 2022
Accredited SINTA 2 by Ministry of Research, Technology, and
Higher Education of The Republic of Indonesia No. 23/E/KPT/2019 on August 8th, 2019 from
October 1st, 2018 to September 30th, 2023

Table 6 Pollution load of TSS existing

Source of waste	Discharge (m ³ /sec)	TSS existing (mg/L)	Pollution Load existing (kg/day)
Washing	0.10	223.20	1928.45
Boiling	0.05	655.20	2830.46
Soaking	0.05	370.00	1598.40
Mixing	0.20	194.40	3359.23

Table 7 Maximum pollution load of TSS

Source of waste	Discharge (m ³ /sec)	TSS standard (mg/L)	Maximum Pollution Load (kg/day)
Washing	0.10	100	864
Boiling	0.05	100	432
Soaking	0.05	100	432
Mixing	0.20	100	1728

Table 8 Allocation pollution load of TSS

Source of waste	Discharge (m ³ /sec)	Pollution Load existing (kg/day)	Maximum Pollution Load (kg/day)	Allocation of Pollution Load (kg/day)
Washing	0.10	1928.45	864	-1064.45
Boiling	0.05	2830.46	432	-2398.46
Soaking	0.05	1598.40	432	-1166.40
Mixing	0.20	3359.23	1728	-1631.23

Highest Pollution load existing in mixing wastes source but the highest allocation of pollution load happened in boiling wastewater. It is depend on TSS concentration and discharge from source. Boiling wastewater of soybean also has high nutrient as nitrogen (Hokamura *et al.*, 2017). Nitrogen effect to the eutrophication in the water (Wang *et al.*, 2019) that makes blooming algae in the surface water and disturb penetration sunlight for photosynthesis. It is impact to decrease of dissolved oxygen then dangerous for aquatic life. Overall of pollution load in wastewater from each stage exceed the maximum pollution load as wastewater tempeh production. It is mean not requirement to the environment and need treatment to improve wastewater quality of TSS. It is showed in allocation pollution load get negative value and

pollution load capacity for TSS content in tempeh wastewater was exceed the standard. High TSS will influence turbidity in the water increase (Seroja, Effendi and Hariyadi, 2018). TSS in the water prevent penetration sunlight that affect photosynthesis process (Puspawati and Soesilo, 2018; Seroja, Effendi and Hariyadi, 2018).

3.3 Pollution Load of BOD

Pollution load existing, maximum pollution load and allocation pollution load of BOD from tempeh industry wastewater showed in Table 9, 10, and 11.

Table 9 Pollution load of BOD existing

Source of waste	Discharge (m ³ /sec)	BOD existing (mg/L)	Pollution Load existing (kg/day)
Washing	0.10	114.77	991.61
Boiling	0.05	174.65	754.49
Soaking	0.05	299.40	1293.41
Mixing	0.20	264.47	4570.04

Table 10 Maximum pollution load of BOD

Source of waste	Discharge (m ³ /sec)	BOD Standard (mg/L)	Maximum Pollution Load (kg/day)
Washing	0.10	150	1296
Boiling	0.05	150	648
Soaking	0.05	150	648
Mixing	0.20	150	2592

Table 11 Allocation pollution load of BOD

Source of waste	Discharge (m ³ /sec)	Pollution Load existing (kg/day)	Maximum Pollution Load (kg/day)	Allocation of Pollution Load (kg/day)
Washing	0.10	991.61	1,296	304.39
Boiling	0.05	754.49	648	-106.49
Soaking	0.05	1,293.41	648	-645.41
Mixing	0.20	4,570.04	2592	-1,978.04

Highest Pollution load existing and allocation of pollution load of BOD happened in mixing waste. All pollution loads have exceeded the standard except washing stage. Oxygen in the water depends on between photosynthesis, degradation organic matter and aeration processes (Ali and Khairy, 2016). BOD is measure dissolved oxygen consumed by microorganisms for degradation process in the wastewater (Bhateria and Jain, 2016). The high discharge and pollution load existing of BOD affect to the high value of BOD allocation pollution load. Discharge of mixing waste is highest that effect increasing pollution load due to high organic matter degradable. Discharge kind of wastewater influence water quality (Elsayed *et al.*, 2019) and pollution load.

3.4 Pollution Load of COD

Pollution load existing, maximum pollution load and allocation pollution load of COD from tempeh industry wastewater showed in Table 12, 13, and 14.

Table 12 Pollution load of COD existing

Source of waste	Discharge (m ³ /sec)	COD existing (mg/L)	Pollution Load existing (kg/day)
Washing	0.10	200.72	1734.22
Boiling	0.05	351.54	1518.65
Soaking	0.05	540.66	2335.65
Mixing	0.20	403.02	6964.19

Table 13 Maximum pollution load of COD

Source of waste	Discharge (m ³ /sec)	COD standard (mg/L)	Maximum Pollution Load (kg/day)
Washing	0.10	300	2592
Boiling	0.05	300	1296
Soaking	0.05	300	1296
Mixing	0.20	300	5184

Table 14 Allocation pollution load of COD

Source of waste	Discharge (m ³ /sec)	Pollution Load existing (kg/day)	Maximum Pollution Load (kg/day)	Allocation of Pollution Load (kg/day)
Washing	0.10	1,734.22	2,592	857.78
Boiling	0.05	1,518.65	1,296	-222.65
Soaking	0.05	2,335.65	1,296	-1,039.65
Mixing	0.20	6,964.19	5,184	-1,780.19

Highest pollution load and allocation pollution load of COD occur in mixing waste, similarly BOD pollution load. It meaning that oxygen needed to organic and inorganic matter degradation by biological and chemical processes. COD usually as important indicator of water pollution for organic matter in the water (Zhang *et al.*, 2020). Kind of wastewater has high COD contents and suspended solid have high organic matter (Apandi *et al.*, 2019). Nutrient and organic pollution load was reduced by microalgae found COD and BOD removal up to 75% and 82% (Usha *et al.*, 2016).

4. CONCLUSION

In identification result of wastewater quality of pH values in all tempeh processing steps were acidic and have exceeded the standard. Highest BOD and COD were showed in soaking step due to there is high organic matter. It has potential to get biogas in wastewater treatment by anaerobic digestion. Then the highest TSS was showed in boiling step due to there is turbulence process during boil of the soybean. Pollution load in parameters have exceed the standard except in washing waste. These findings indicated that tempeh production wastewater is capable to impact the aquatic life balance. Wastewater from tempeh industry should be treated in order to reduce its impact in aquatic environment.

5. ACKNOWLEDGEMENT

The authors thank to Health and Environmental Chemical Laboratory, East Kalimantan for helping analysis the sample.

REFERENCES

- Ahnan-Winarno, A. D. *et al.*, 2021. Tempeh : A Semicentennial Review on its Health Benefits, Fermentation, Safety, Processing, Sustainability, and Affordability. *Comprehensive Review in Food Science and Food Safety*, 20 (December 2020), pp. 1717–1767. Doi: 10.1111/1541-4337.12710.
- Ali, E. M. and Khairy, H. M. 2016. Environmental Assessment of Drainage Water Impacts on Water Quality and Eutrophication Level of Lake Idku, Egypt'. *Environmental Pollution*. Doi: 10.1016/j.envpol.2016.05.064.
- Apandi, N. M. *et al.*, 2019. Microalgal Biomass Production through Phycoremediation of Fresh Market Wastewater and Potential Applications as Aquaculture Feeds. *Environmental Science and Pollution Research*. 26(4): 3226-3242. Doi: 10.1007/s11356-018-3937-3.
- Bhateria, R. and Jain, D. 2016. Water Quality Assessment of Lake Water: A Review. *Sustainable Water Resources Management*. 2(2): 161-173. Doi: 10.1007/s40899-015-0014-7.
- Chua, J. Y. and Liu, S. Q. 2019. Soy whey: More than just Wastewater from Tofu and Soy Protein Isolate Industry. *Trends in Food Science and Technology*. 91, pp. 24-32. Doi: 10.1016/j.tifs.2019.06.016.
- Elsayed, F. A. *et al.* 2019. Nutrient Salts and Eutrophication Assessment in Northern Delta Lakes: Case Study Burullus Lake, Egypt. *Egyptian Journal of Aquatic Biology & Fisheries*. 23(2): 145-163.
- Fransiscus, Y. and Simangunsong, T. L. 2021. Anaerobic Digestion of Industrial Tempeh Wastewater with Sludge from Cow Manure Biogas Digester as Inoculum: Effect of F/M Ratio on the Methane Production. *International Journal on Advanced Science, Engineering and Information Technology*. (July): 856-863. Doi: 10.18517/ijaseit.11.3.9667.
- Government Regulation. 2011. Local Government Regulation of East Kalimantan Province No. 2 Years 2011 regarding water Quality Management and Water Pollution Control. Local Government of East Kalimantan Province.
- Guo, K. *et al.*, 2018. Study on the Treatment of Soybean Protein Wastewater by a Pilot-Scale IC-A/O Coupling Reactor. *Chemical Engineering Journal*. 343 (January): 189-197. Doi: 10.1016/j.cej.2018.02.128.
- Hokamura, A. *et al.*, 2017. Biosynthesis of Polyhydroxyalkanoate from Steamed Soybean Wastewater by a recombinant Strain of *Pseudomonas* sp. 61-3. *Bioengineering*. 4(3). Doi: 10.3390/bioengineering4030068.
- Mamun, M., Lee, S. J. and An, K. G. 2018. Temporal and Spatial Variation of Nutrients, Suspended Solids, and Chlorophyll in Yeongsan Watershed. *Journal of Asia-Pacific Biodiversity*. 11(2): 206-216. Doi: 10.1016/j.japb.2018.02.006.

- Pramaningsih, V. *et al.*, 2020. Pollution Load Capacity Analysis of BOD, COD, and TSS in Karang Mumus River, Samarinda. *Indones. J. Chem.* 20(3): 626-637. Doi: 10.22146/ijc.44296.
- Puspawati, S. W. and Soesilo, T. E. B. 2018. Sustainable Approach to Tempeh Industrial Wastewater Management in Karawang. *E3S Web of Conferences.* 74: 1-7. Doi: 10.1051/e3sconf/20187409003.
- Raudsepp, U. *et al.*, 2019. Science of the Total Environment Shipborne Nutrient Dynamics and Impact on the Eutrophication in the Baltic Sea. *Science of the Total Environment.* 671: 189-207. Doi: 10.1016/j.scitotenv.2019.03.264.
- Santhirasegaram, V. *et al.*, 2016. Effects of Soybean Processing and Packaging on the Quality of Commonly Consumed Local Delicacy Tempe. *Journal of Food Quality.* 39(6): 675-684. Doi: 10.1111/jfq.12252.
- Seroja, R., Effendi, H. and Hariyadi, S. 2018. Tofu Wastewater Treatment using Vetiver Grass (*Vetiveria zizanioides*) and Zeliac. *Applied Water Science.* 8(1): 1-6. Doi: 10.1007/s13201-018-0640-y.
- Song, C. *et al.*, 2019. A Novel Concept of Bicarbonate-Carbon Utilization via an Absorption-Microalgae Hybrid Process Assisted with Nutrient Recycling from Soybean Wastewater. *Journal of Cleaner Production.* 237: 117864. doi: 10.1016/j.jclepro.2019.117864.
- Song, C. *et al.*, 2020. Microalgae Carbon Fixation Integrated with Organic Matters Recycling from Soybean Wastewater: Effect of pH on the Performance of Hybrid System. *Chemosphere*, 248, p. 126094. Doi: 10.1016/j.chemosphere.2020.126094.
- State Minister of Environment. 2003. Decision State Minister of the Environment No. 110 Years 2003 about Guidelines for Determination of Load Capacity Water Pollution in Water Source.
- Usha, M. *et al.*, 2016. Removal of Nutrients and Organic Pollution Load from Pulp and Paper Mill Effluent by Microalgae in Outdoor Open Pond. 214(August): 856-860. Doi: <https://doi.org/10.1016/j.biortech.2016.04.060>.
- Wang, J. *et al.*, 2019. Assessment of Eutrophication and Water Quality in the Estuarine Area of Lake Wuli, Lake Taihu, China. *Science of the Total Environment.* 650: 1392-1402. Doi: 10.1016/j.scitotenv.2018.09.137.
- Wang, Y. and Serventi, L. 2019. Sustainability of Dairy and Soy Processing: A Review on Wastewater Recycling. *Journal of Cleaner Production.* 237. Doi: 10.1016/j.jclepro.2019.117821.
- Wijaya, S. 2019. Indonesian Food Culture Mapping: A Starter Contribution to Promote Indonesian Culinary Tourism. *Journal of Ethnic Foods.* 6(1): 1–10. Doi: 10.1186/s42779-019-0009-3.

Wastewater Quality and Pollution Load of Each Stage in Tempeh Production

Pramaningsih, Hansen, Praveena, Styana
p-ISSN 2579-9150; e-ISSN 2579-9207, Volume 5, Number 3, page 209-222, October 2022
Accredited SINTA 2 by Ministry of Research, Technology, and
Higher Education of The Republic of Indonesia No. 23/E/KPT/2019 on August 8th, 2019 from
October 1st, 2018 to September 30th, 2023

- Yu, N. *et al.*, 2017. Electricity and Methane Production from Soybean Edible Oil Refinery Wastewater using Microbial Electrochemical Systems. *International Journal of Hydrogen Energy*. 42(1): 96-102. Doi: 10.1016/j.ijhydene.2016.11.116.
- Yu, Y. 2015. Research on Soybean Protein Wastewater Treatment by the Integrated Two-Phase Anaerobic Reactor. *Saudi Journal of Biological Sciences*. 22(5): 526-531. Doi: 10.1016/j.sjbs.2015.01.006.
- Zhang, H. *et al.*, 2020. Water Quality Assessment and Pollution Source Apportionment using Multi-Statistic and APCS-MLR Modeling Techniques in Min River Basin, China. *Environmental Science and Pollution Research*. 27(33): 41987–42000. Doi: 10.1007/s11356-020-10219-y.
- Zhang, J., Zhang, Y. and Diao, N. 2017. Combined Approach for Soybean Wastewater Chemical Oxygen Demand Reduction using *Aspergillus Niger* Pelletization Technology. *Biotechnology & Biotechnological Equipment*. 31(2): 318-324. Doi: 10.1080/13102818.2016.1262751.
- Zhu, J. *et al.*, 2014. Solid-State Anaerobic Co-Digestion of Hay and Soybean Processing Waste for Biogas Production. *Bioresour Technol*. 154: 240-247. Doi: 10.1016/j.biortech.2013.12.045.

WASTEWATER QUALITY AND POLLUTION LOAD OF EACH STAGE IN TEMPEH PRODUCTION

ORIGINALITY REPORT

10%

SIMILARITY INDEX

4%

INTERNET SOURCES

8%

PUBLICATIONS

2%

STUDENT PAPERS

PRIMARY SOURCES

- | | | |
|---|--|-----|
| 1 | C Irawan, S Yuniar, H Khotimah, IF Nata, MD Putra. "High Adsorption Capacity of Activated Carbon from Rubber Seed Shells on Tofu (Soybean Whey) Wastewater", IOP Conference Series: Earth and Environmental Science, 2020
Publication | 3% |
| 2 | digilib.uinsby.ac.id
Internet Source | 2% |
| 3 | N Lusiana, B Rahadi, Y Anggita. "Determination pollution load capacity of Ngrowo River as wastewater receiver from hospital activities", IOP Conference Series: Earth and Environmental Science, 2020
Publication | 1% |
| 4 | ijcrar.com
Internet Source | <1% |
| 5 | Jiying Zhu, Yi Zheng, Fuqing Xu, Yebo Li. "Solid-state anaerobic co-digestion of hay and soybean processing waste for biogas production", Bioresource Technology, 2014 | <1% |

6	www.exim.gov Internet Source	<1 %
7	Submitted to Universitas Katolik De La Salle Student Paper	<1 %
8	pubmed.ncbi.nlm.nih.gov Internet Source	<1 %
9	www.researcherslinks.com Internet Source	<1 %
10	Jian-Yong Chua, Shao-Quan Liu. "Soy whey: More than just wastewater from tofu and soy protein isolate industry", Trends in Food Science & Technology, 2019 Publication	<1 %
11	techno-press.com Internet Source	<1 %
12	www.tsijournals.com Internet Source	<1 %
13	Darwin, I Wayan Koko Suryawan, Gita Prajati. "Evaluation of Waste Stabilization Pond (WSP) Performance in Bali Tourism Area", 2019 2nd International Conference on Applied Engineering (ICAE), 2019 Publication	<1 %
14	M.T. Usha, T. Sarat Chandra, R. Sarada, V.S. Chauhan. "Removal of nutrients and organic	<1 %

pollution load from pulp and paper mill effluent by microalgae in outdoor open pond", Bioresource Technology, 2016

Publication

15

ijmse.iust.ac.ir

Internet Source

<1 %

16

Purwo Setiyo Nugroho, Ratu Matahari, Sri Sunarti. "Fertility Situation among Urban and Rural Residents in Indonesia; Based on Indonesian Census 2010", BIO Web of Conferences, 2022

Publication

<1 %

Exclude quotes On

Exclude matches Off

Exclude bibliography On